



Maximum Performance



# VALUE LINE

[UNIMAC.COM](http://UNIMAC.COM)

**UW45 & UW65 POCKET HARDMOUNT WASHER-EXTRACTORS**

## WHERE BRAND-NEW MEETS VALUE

As the leading manufacturer of on-premises laundry equipment, UniMac® offers more than 7 decades of incomparable quality and long-lasting performance. Our UW series is built with unyielding construction to ensure industrial strength. Our cutting-edge innovations and technologies reduce costs and maximize throughput. And we're constantly improving. It's all part of our commitment to providing the lowest cost of ownership in the industry.

Our UW washer-extractors are renowned for their durability, innovative features and industrial strength. Our Value Line of UW45 & 65 models will provide you with exactly that – all while fitting your budget. They are designed to run 24/7, built for the heaviest OPL use and last longer than ever before. A five-year warranty covers the frame, basket, shaft, bearings and seals from failure or breakage during normal operation due to defects in material or workmanship. A limited three-year warranty is offered on all other parts.

SPECIFICATIONS		UW45		UW65	
Control Options		M30		M30	
Capacity - lb (kg)		45 (20)		65 (30)	
Cylinder Diameter - in (mm)		31 (787)		31 (787)	
Cylinder Depth - in (mm)		16.6 (422)		22.1 (561)	
Cylinder Volume - cu ft (liters)		7.3 (207)		9.7 (275)	
Height - in (mm)		64.7 (1643)		64.7 (1643)	
Width - in (mm)		34.1 (866)		34.1 (866)	
Depth - in (mm)		45.3 (1151)		51.1 (1298)	
Door Opening Size - in (mm)		17.8 (452)		17.8 (452)	
Door Bottom to Floor - in (mm)		21.4 (544)		21.4 (544)	
Motor Size - HP (kW)		5 (3.7)		5 (3.7)	
Total # of Speeds		L Sp	M Sp	L Sp	M Sp
		5	6	5	6
Cylinder Speed RPM ( G-Force)	Gentle	30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)
	Wash	42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)
	Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)
	Very Low	248 (27)	248 (27)	248 (27)	248 (27)
	Low	477 (100)	477 (100)	477 (100)	477 (100)
	Medium	-	674 (200)	-	674 (200)
Drain Diameter - in (mm)		3 (76)		3 (76)	
Steam Connection - in (mm)		½ (13)		½ (13)	
Water Inlet Connection - in (mm)		4 @ ¾ (19)		4 @ ¾ (19)	
Shipping Dimensions - in (mm)	Width	37.2 (945)		37.2 (945)	
	Depth	53.8 (1370)		53.8 (1370)	
	Height	65 (1650)		65 (1650)	
Net Weight - lb (kg)		1080 (490)		1110 (499)	
Standard Shipping Weight - lb (kg)		1120 (508)		1150 (522)	
Slat Crate Shipping Weight - lb (kg)		1250 (567)		1280 (581)	
Agency Approvals		cULus		cULus	

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility have been registered to ISO 9001:2008.

## UW SERIES – AT A GLANCE

- Industrial construction is built to run 24/7
- Helps reduce drying time and increase through-put with a 200 g-force extraction
- Bigger motor has 67% more horsepower than cabinet washer-extractors
- Handles unbalanced loads effortlessly
- 34.12" Width easily fits through 36" commercial doorways
- 30 Programmable cycles
- Perforated cylinder ribs maximize wash action
- Auto leak detection greatly reduces water loss due to valve blockages or failures
- Easier installation with vertical access to six frame bolts

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM**

**ALLIANCE LAUNDRY SYSTEMS  
SHEPARD ST, RIPON, WI 54971  
1.800.587.5458**



Proudly based in Ripon, Wisconsin, USA, UniMac is dedicated to research, development and testing to provide equipment that delivers industrial strength and long-lasting quality. Our products undergo a 5-stage product-development process and are pushed beyond their limits in our state-of-the-art test lab to ensure they exceed the toughest demands of the commercial environment and meet our customers' highest standards.